



## CX-ED1079 SERIES: 'UNIVERSAL' LOW & STANDARD PROFILE GRADE 1 ELECTRIC STRIKES

**CX-ED1079** (low profile, for 5/8" latch projection) and **CX-ED1079D** (standard depth, for 3/4" latch projection) 'Universal' grade 1 ANSI strikes offer 'Universal' performance with selectable 12/24V AC/DC and fail safe/fail secure operation, and have horizontal faceplate/body adjustment. Both models have optional latch monitoring.



### Features

- Centerline latch entry for cylindrical and mortise locksets
- CX-ED1079, low profile. 1/2" to 5/8" latch projection (throw)
- CX-ED1079D, standard depth. 5/8" to 3/4" latch projection (throw)
- Selectable 12/24V AC/DC
- Selectable fail safe/fail secure operation
- Horizontal adjustability of strike body
- 3 stainless steel faceplates included: ANSI square, hollow metal and wood door frame
- Continuous duty operation
- Non-handed
- ANSI/BHMA A156.31, Grade 1 certified
- 5 year warranty



### MODELS

		List Price
CX-ED1079	Low profile Grade 1 'Universal' electric strike, 12/24V AC/DC, fail safe/fail secure operation, horizontal adjustment, and 3 stainless steel faceplates (CX-ESP1B, CX-ESP3B & CX-ESP4B)	\$260.00
CX-ED1079L	As above, with latch monitoring	\$280.00
CX-ED1079D	Standard depth Grade 1 'Universal' electric strike, 12/24V AC/DC, fail safe/fail secure operation, horizontal adjustment, and 3 stainless steel faceplates (CX-ESP1B, CX-ESP3B & CX-ESP4B)	\$260.00
CX-ED1079DL	As above, with latch monitoring	\$280.00
CX-ED1079-BK	Low profile Grade 1 'Universal' electric strike, 12/24V AC/DC, fail safe/fail secure operation, horizontal adjustment, and 3 black faceplates (CX-ESP1B-BK, CX-ESP3B-BK & CX-ESP4B-BK)	\$293.00
CX-ED1079L-BK	As above, with latch monitoring	\$313.00
CX-ED1079D-BK	Standard depth Grade 1 'Universal' electric strike, 12/24V AC/DC, fail safe/fail secure operation, horizontal adjustment, and 3 black faceplates (CX-ESP1B-BK, CX-ESP3B-BK & CX-ESP4B-BK)	\$293.00
CX-ED1079DL-BK	As above, with latch monitoring	\$313.00

### FACEPLATES

		List Price
CX-ESP1B	ANSI Square, 4-7/8" x 1-1/4", stainless steel	\$23.00
CX-ESP3B	Hollow Metal Door, 6-7/8" x 1-1/4", stainless steel	\$25.00
CX-ESP4B	Wood Door, 7-15/16" x 1-7/16", stainless steel	\$27.00
CX-ESP2B	ANSI Round, 4-7/8" x 1-1/4", stainless steel	\$23.00
CX-ESP1B-BK	ANSI Square, 4-7/8" x 1-1/4", all-black finish (BHMA 622, US19)	\$58.00
CX-ESP2B-BK	ANSI Round, 4-7/8" x 1-1/4", all-black finish (BHMA 622, US19)	\$58.00
CX-ESP3B-BK	Hollow Metal Door, 6-7/8" x 1-1/4", all-black finish (BHMA 622, US19)	\$58.00
CX-ESP4B-BK	Wood Door, 7-15/16" x 1-7/16", all-black finish (BHMA 622, US19)	\$58.00

### LIP EXTENSION BRACKETS

		List Price
CX-ED-LIP1	1" Lip extension for ANSI strikes (stackable)	\$36.00
CX-ED-LIP2	2" Lip extension for ANSI strikes	\$40.00

### Specifications

Voltage:	12/24V AC/DC
Current Draw:	260mA @ 12V AC/DC 150mA @ 24V AC/DC
Static Strength:	1,500 lbs.
Dynamic Strength:	70 Ft- lbs.
Mode:	Selectable Fail safe/Fail-secure
Endurance:	1,000,000 Cycles (Factory Tested) 500,000 Cycles (UL Verified)
Operation:	AC - Buzz   DC - Silent
Duty:	Continuous
Latch Monitor	SPDT, 100mA @ 24 VDC
Dimensions:	<b>CX-ED1079:</b> 4-7/8"H x 1-7/8"W x 1-7/32"D (124mm x 47mm x 31mm) <b>CX-ED1079D:</b> 4-7/8"H x 1-7/8"W x 1-3/8"D (124mm x 47mm x 35mm)