



## CX-ED2071/CX-ED2079: 'UNIVERSAL' LOW PROFILE GRADE 2 ELECTRIC STRIKES

**CX-ED2071** low profile grade 2 ANSI electric strike for cylindrical locksets provides exceptional value for installations that require 8-16V AC/DC operation. It includes 3 faceplates, selectable fail safe/fail secure operation and horizontal adjustment of the strike body.

**CX-ED2079** low profile 'Universal' grade 2 ANSI electric strike for cylindrical locksets provides exceptional value with 3 faceplates, and selectable 12/24V AC/DC voltage, fail safe/fail secure operation and horizontal adjustment of the strike body.

**CX-ED2079-1** Low profile 'Universal' grade 2 ANSI strike for cylindrical locksets, with (1) ANSI square faceplate, provides the best strike value.



**BHMA**  
CERTIFIED



CX-ED2071/  
CX-ED2079

### Features

- Centerline latch entry for cylindrical locksets, 1/2" to 5/8" latch projection
- Horizontal adjustability of strike body
- Low profile strike body
- Selectable fail safe/fail secure
- ANSI/BHMA A156.31, Grade 1 certified (CX-ED2079 Series)
- 5 year warranty
- CX-ED2079: 12/24V strike, includes (3) stainless steel faceplates: ANSI square, hollow metal door and wood door
- CX-ED2079-1: 12/24V strike, includes (1) stainless steel ANSI square faceplate
- CX-ED2071: 8V - 16V strike, includes (3) stainless steel faceplates ANSI square, hollow metal door, and wood door

### MODELS

		List Price
CX-ED2071	'Universal' electric strike, 8 - 16V AC/DC, fail safe/fail secure operation, horizontal adjustment, w/ 3 stainless steel faceplates (CX-ESP1B, ESP3B & ESP4B)	\$235.00
CX-ED2079*	'Universal' electric strike, 12/24V AC/DC, fail safe/fail secure operation, horizontal adjustment, w/ 3 stainless steel faceplates (CX-ESP1B, ESP3B & ESP4B)	\$230.00
CX-ED2079-1*	'Universal' electric strike, 12/24V AC/DC, fail safe/fail secure operation, horizontal adjustment, w/ 1 stainless steel faceplate (EX-ESP1B)	\$210.00
CX-ED2071-BK	'Universal' electric strike, 8 - 16V AC/DC, fail safe/fail secure operation, horizontal adjustment, w/ 3 black faceplates (CX-ESP1B-BK, ESP3B-BK & ESP4B-BK)	\$246.00
CX-ED2079-BK*	'Universal' electric strike, 12/24V AC/DC, fail safe/fail secure operation, horizontal adjustment, w/ 3 black faceplates (CX-ESP1B-BK, ESP3B-BK & ESP4B-BK)	\$260.00
CX-ED2079-1-BK*	'Universal' electric strike, 12/24V AC/DC, fail safe/fail secure operation, horizontal adjustment, w/ 1 black faceplate (EX-ESP1B-BK)	\$240.00

### FACEPLATES

		List Price
<b>Included In Package</b>		
CX-ESP1B	ANSI Square, 4-7/8" x 1-1/4", stainless steel	\$23.00
CX-ESP3B	Hollow Metal Door, 6-7/8" x 1-1/4", stainless steel	\$25.00
CX-ESP4B	Wood Door, 7-15/16" x 1-7/16", stainless steel	\$27.00

### Optional Faceplates

CX-ESP2B	ANSI Round, 4-7/8" x 1-1/4", stainless steel	\$23.00
CX-ESP1B-BK	ANSI Square, 4-7/8" x 1-1/4", all-black finish (BHMA 622, US19)	\$58.00
CX-ESP2B-BK	ANSI Round, 4-7/8" x 1-1/4", all-black finish (BHMA 622, US19)	\$58.00
CX-ESP3B-BK	Hollow Metal Door, 6-7/8" x 1-1/4", all-black finish (BHMA 622, US19)	\$58.00
CX-ESP4B-BK	Wood Door, 7-15/16" x 1-7/16", all-black finish (BHMA 622, US19)	\$58.00

### LIP EXTENSION BRACKETS

		List Price
CX-ED-LIP1	1" Lip extension for ANSI strikes (Stackable)	\$36.00
CX-ED-LIP2	2" Lip extension for ANSI strikes	\$40.00

### Specifications

Voltage:	<b>CX-ED2071:</b> 8 - 16V, AC/DC <b>CX-ED2079:</b> 12/24V, AC/DC
Current Draw:	<b>CX-ED2071:</b> 305mA @ 8 VDC, 625mA @ 16 VDC <b>CX-ED2079:</b> 190mA @ 8 VAC, 460mA @ 16 VAC
Static Strength:	1000 lbs.
Dynamic Strength:	50 Ft. lbs.
Mode:	Selectable fail safe/fail secure
Endurance:	<b>CX-ED2071:</b> 700,000 cycles (Factory Tested) 250,000 cycles (UL Verified) <b>CX-ED2079:</b> 700,000 cycles (Factory Tested) 500,000 cycles (UL Verified)
Operation:	AC - Buzz   DC - Silent
Duty:	<b>CX-ED2071:</b> Intermittent <b>CX-ED2079:</b> Continuous
Mounting:	Non-handed
Dimensions (Body):	4-7/8"H x 1-7/8"W x 1-7/32"D (124mm x 47mm x 31mm)

