



# ELECTRIC STRIKES

## LOCKING PRODUCTS

### CX-ED1689L & CX-ED1799L SERIES: LOW PROFILE & DUAL MONITOR 'ALL IN ONE' FIRE RATED ELECTRIC STRIKES

Camden CX-ED1689L and CX-ED1799L are Grade 1 fire rated "all in one" electric strikes for use with mortise and cylindrical locksets. Both models include latch monitoring, and are packaged with either 4 or 8 faceplates. 'Universal' performance, with field selectable voltage and fail safe/fail secure operation.

Option for ordering strike bodies and individual faceplates separately. Faceplates also available in black finish.



**BHMA**  
CERTIFIED



CX-ED1689L\*



CX-ED1799L\*\*

#### Features

- For mortise and cylindrical locksets
- A range of strike and faceplate packages for latchbolts and deadbolts
- Faceplates also available in black architectural finish (BHMA 622, US19)
- Selectable fail safe/fail secure
- Selectable 12/24V AC/DC
- 1 or 2 latch and deadbolt monitoring switches included
- Magnetic door position switch included
- Strike power monitor switches included
- Easy fit connectors
- ANSI/BHMA A156.31, Grade 1 certified
- 5 year warranty

ELECTRIC STRIKES WITHOUT FACEPLATES		List Price
CX-ED1689L	Low Profile Strike Body with Latch Monitor Switch. Order Faceplates Separately.	\$600.00
CX-ED1799L	Strike Body with Latch & Deadbolt Monitor Switches. Order Faceplates Separately.	\$625.00
STRIKE AND MULTI FACEPLATE PACKS		List Price
Low Profile		
CX-ED1689L-4	Strike w/ Latch Monitor, (4) Faceplates for Latchbolts Includes: CX-EMP100, CX-EMP200, CX-EMP300, CX-EMP400	\$700.00
CX-ED1689L-4-BK	Strike w/ Latch Monitor, (4) Black Faceplates for Latchbolts Includes: CX-EMP100-BK, CX-EMP200-BK CX-EMP300-BK, CX-EMP400-BK	\$760.00
Standard Depth Dual Monitor		
CX-ED1799L-8	Strike w/ 2 Monitors, (8) Faceplate Package for Latchbolts & Deadbolts Includes: CX-EMP100, CX-EMP200, CX-EMP300, CX-EMP400, CX-EMP110, CX-EMP210, CX-EMP310, CX-EMP410	\$750.00
CX-ED1799L-8-BK	Strike w/ 2 Monitors, (8) Black Faceplate Package for Latchbolts & Deadbolts Includes: CX-EMP100-BK, CX-EMP200-BK, CX-EMP300-BK, CX-EMP400-BK, CX-EMP110-BK, CX-EMP210-BK, CX-EMP310-BK, CX-EMP410-BK	\$870.00

#### Specifications

Voltage:	12/24V AC/DC
Current Draw:	300mA @ 12V AC/DC 150mA @ 24V AC/DC
Static Strength:	1,500 lbs.
Dynamic Strength:	70 Ft. lbs.
Mode:	Selectable Fail Safe/Fail Secure
Endurance:	1,500,000 Cycles (Factory Tested) 500,000 Cycles (UL Verified)
Operation:	AC - Buzz   DC - Silent
Duty:	Continuous
Fire Rating:	UL 10C/CAN4-S104   3hr. (Fail Safe)
Lock Monitor Status:	2 x SPST, 100mA @ 24 VDC, Resistive
Strike Monitor Status:	SPDT, 100mA @ 24 V DC, Resistive
Dimensions:	<b>CX-ED1689L:</b> 4-7/8" H x 1-5/8" W x 1-3/8" D (124mm x 41mm x 36mm) <b>CX-ED1799L:</b> 4-7/8" H x 1-5/8" W x 1-21/32" D (124mm x 41mm x 42mm)