



CX-ED1259L
SURFACE MOUNT
RIM ELECTRIC STRIKE

STANDARD FEATURES	CAMDEN CX-ED1259L	RCI-0563	HES-9600	HES-9500	HES-9400	TRINE 4800F	SECO LARM SD-998C-NUQ	VON DUPRIN 6300
Heavy Duty Stainless steel construction	√	√	√	√	√	√	X	√
1/2" Low Profile Design	√	√	X	X	√	X	X	X
Fire label 10C 3 Hr	√	X	X	√	X	√	X	√
UL1034 Burglary Resistant	√	√	√	√	√	√	√	√
Tested to ANSI-Grade 1	√	√	√	√	√	√	√	√
Plug in wire connectors	√	√	√	√	√	√	√	X
Dual voltage	√	√	√	√	√	√	√	√
Monitor switch standard	√	X	X	X	X	X	X	X
Non Handed	√	√	√	√	√	√	√	√
Adjustable for different latch/frame spacing	√	√	X	X	√	X	X	X
Standard cover plate	√	X	√	√	√	X	X	X
Spacer plates included for 5/8" - 3/4" install	√	X	X	X	X	√	X	X
Endurance cycles	2,000.000	100,000	1,000.000	1,000.000	500,000	1,500.000	250,000	2,000.000

Note: Specifications are subject to change without notice. (FEBRUARY 5, 2018)