



CX-ED2071/CX-ED2079: 'UNIVERSAL' LOW PROFILE GRADE 2 ELECTRIC STRIKES

CX-ED2071 low profile grade 2 ANSI electric strike for cylindrical locksets provides exceptional value for installations that require 8-16V AC/DC operation. It includes 3 faceplates, selectable fail safe/fail secure operation and horizontal adjustment of the strike body.

CX-ED2079 low profile 'Universal' grade 2 ANSI electric strike for cylindrical locksets provides exceptional value with 3 faceplates, and selectable 12/24V AC/DC voltage, fail safe/fail secure operation and horizontal adjustment of the strike body.

CX-ED2079-1 Low profile 'Universal' grade 2 ANSI strike for cylindrical locksets, with (1) ANSI square faceplate, provides the best strike value.



BHMA
CERTIFIED



CX-ED2071/
CX-ED2079

Features

- Centerline latch entry for cylindrical locksets, 1/2" to 5/8" latch projection
- Horizontal adjustability of strike body
- Low profile strike body
- Selectable fail safe/fail secure
- ANSI/BHMA A156.31, Grade 1 certified (CX-ED2079 Series)
- 5 year warranty
- CX-ED2079: 12/24V strike, includes (3) stainless steel faceplates: ANSI square, hollow metal door and wood door
- CX-ED2079-1: 12/24V strike, includes (1) stainless steel ANSI square faceplate
- CX-ED2071: 8V - 16V strike, includes (3) stainless steel faceplates ANSI square, hollow metal door, and wood door

MODELS

| | | List Price |
|-----------------|---|------------|
| CX-ED2071 | 'Universal' electric strike, 8 - 16V AC/DC, fail safe/fail secure operation, horizontal adjustment, w/ 3 stainless steel faceplates (CX-ESP1B, ESP3B & ESP4B) | \$215.00 |
| CX-ED2079* | 'Universal' electric strike, 12/24V AC/DC, fail safe/fail secure operation, horizontal adjustment, w/ 3 stainless steel faceplates (CX-ESP1B, ESP3B & ESP4B) | \$205.00 |
| CX-ED2079-1* | 'Universal' electric strike, 12/24V AC/DC, fail safe/fail secure operation, horizontal adjustment, w/ 1 stainless steel faceplate (EX-ESP1B) | \$185.00 |
| CX-ED2071-BK | 'Universal' electric strike, 8 - 16V AC/DC, fail safe/fail secure operation, horizontal adjustment, w/ 3 black faceplates (CX-ESP1B-BK, ESP3B-BK & ESP4B-BK) | \$226.00 |
| CX-ED2079-BK* | 'Universal' electric strike, 12/24V AC/DC, fail safe/fail secure operation, horizontal adjustment, w/ 3 black faceplates (CX-ESP1B-BK, ESP3B-BK & ESP4B-BK) | \$226.00 |
| CX-ED2079-1-BK* | 'Universal' electric strike, 12/24V AC/DC, fail safe/fail secure operation, horizontal adjustment, w/ 1 black faceplate (EX-ESP1B-BK) | \$211.00 |

FACEPLATES

| | | List Price |
|----------------------------|---|------------|
| Included In Package | | |
| CX-ESP1B | ANSI Square, 4-7/8" x 1-1/4", stainless steel | \$23.00 |
| CX-ESP3B | Hollow Metal Door, 6-7/8" x 1-1/4", stainless steel | \$25.00 |
| CX-ESP4B | Wood Door, 7-15/16" x 1-7/16", stainless steel | \$27.00 |

Optional Faceplates

| | | |
|-------------|---|---------|
| CX-ESP2B | ANSI Round, 4-7/8" x 1-1/4", stainless steel | \$23.00 |
| CX-ESP1B-BK | ANSI Square, 4-7/8" x 1-1/4", all-black finish (BHMA 622, US19) | \$47.00 |
| CX-ESP2B-BK | ANSI Round, 4-7/8" x 1-1/4", all-black finish (BHMA 622, US19) | \$47.00 |
| CX-ESP3B-BK | Hollow Metal Door, 6-7/8" x 1-1/4", all-black finish (BHMA 622, US19) | \$47.00 |
| CX-ESP4B-BK | Wood Door, 7-15/16" x 1-7/16", all-black finish (BHMA 622, US19) | \$47.00 |

LIP EXTENSION BRACKETS

| | | List Price |
|------------|---|------------|
| CX-ED-LIP1 | 1" Lip extension for ANSI strikes (Stackable) | \$27.00 |
| CX-ED-LIP2 | 2" Lip extension for ANSI strikes | \$32.00 |

Specifications

| | |
|--------------------|--|
| Voltage: | CX-ED2071: 8 - 16V, AC/DC CX-ED2079: 12/24V, AC/DC |
| Current Draw: | CX-ED2071: 305mA @ 8 VDC, 625mA @ 16 VDC CX-ED2079: 190mA @ 8 VAC, 460mA @ 16 VAC |
| Static Strength: | 1000 lbs. |
| Dynamic Strength: | 50 Ft. lbs. |
| Mode: | Selectable fail safe/fail secure |
| Endurance: | CX-ED2071: 700,000 cycles (Factory Tested) 250,000 cycles (UL Verified) CX-ED2079: 700,000 cycles (Factory Tested) 500,000 cycles (UL Verified) |
| Operation: | AC - Buzz DC - Silent |
| Duty: | CX-ED2071: Intermittent CX-ED2079: Continuous |
| Mounting: | Non-handed |
| Dimensions (Body): | 4-7/8"H x 1-7/8"W x 1-7/32"D (124mm x 47mm x 31mm) |

