



CX-ED1079 SERIES: 'UNIVERSAL' LOW & STANDARD PROFILE GRADE 1 ELECTRIC STRIKES

CX-ED1079 (low profile, for 5/8" latch projection) and CX-ED1079D (standard depth, for 3/4" latch projection) 'Universal' grade 1 ANSI strikes offer 'universal' performance with selectable 12/24V AC/DC and fail safe/fail secure operation, and have horizontal faceplate/body adjustment. Both models have optional latch monitoring.

Features	
<ul style="list-style-type: none"> Centerline latch entry for cylindrical and mortise locksets CX-ED1079, low profile. 1/2" to 5/8" latch projection (throw) CX-ED1079D, standard depth. 5/8" to 3/4" latch projection (throw) Selectable 12/24V AC/DC Selectable fail safe / fail secure operation 	<ul style="list-style-type: none"> Horizontal adjustability of strike body 3 stainless steel faceplates included: ANSI square, hollow metal and wood door frame Continuous duty operation Non-handed 5 year warranty



MODELS		List Price
CX-ED1079	Low Profile Grade 1 'Universal' electric strike, 12/24V AC/DC, fail safe / fail secure operation, horizontal adjustment, and 3 stainless steel faceplates (CX-ESP1B, CX-ESP3B & CX-ESP4B)	\$210.00
CX-ED1079L	As above, with latch monitoring	\$230.00
CX-ED1079D	Standard Depth Grade 1 'Universal' electric strike, 12/24V AC/DC, fail safe / fail secure operation, horizontal adjustment, and 3 stainless steel faceplates (CX-ESP1B, CX-ESP3B & CX-ESP4B)	\$210.00
CX-ED1079DL	As above, with latch monitoring	\$230.00
CX-ED1079-BK	Low Profile Grade 1 'Universal' electric strike, 12/24V AC/DC, fail safe / fail secure operation, horizontal adjustment, and 3 black faceplates (CX-ESP1B-BK, CX-ESP3B-BK & CX-ESP4B-BK)	\$246.00
CX-ED1079L-BK	As above, with latch monitoring	\$266.00
CX-ED1079D-BK	Standard Depth Grade 1 'Universal' electric strike, 12/24V AC/DC, fail safe / fail secure operation, horizontal adjustment, and 3 black faceplates (CX-ESP1B-BK, CX-ESP3B-BK & CX-ESP4B-BK)	\$246.00
CX-ED1079DL-BK	As above, with latch monitoring	\$266.00
FACEPLATES		List Price
CX-ESP1B	ANSI Square, 4-7/8" x 1-1/4", stainless steel	\$23.00
CX-ESP3B	Hollow Metal Door, 6-7/8" x 1-1/4", stainless steel	\$25.00
CX-ESP4B	Wood Door, 7-15/16" x 1-7/16", stainless steel	\$27.00
CX-ESP2B	ANSI Round, 4-7/8" x 1-1/4", stainless steel	\$23.00
CX-ESP1B-BK	ANSI Square, 4-7/8" x 1-1/4", all-black finish (BHMA 622, US19)	\$58.00
CX-ESP2B-BK	ANSI Round, 4-7/8" x 1-1/4", all-black finish (BHMA 622, US19)	\$58.00
CX-ESP3B-BK	Hollow Metal Door, 6-7/8" x 1-1/4", all-black finish (BHMA 622, US19)	\$58.00
CX-ESP4B-BK	Wood Door, 7-15/16" x 1-7/16", all-black finish (BHMA 622, US19)	\$58.00
LIP EXTENSION BRACKETS		List Price
CX-ED-LIP1	1" Lip extension for ANSI strikes (stackable)	\$36.00
CX-ED-LIP2	2" Lip extension for ANSI strikes	\$40.00

Specifications

Voltage:	12/24V AC/DC
Current Draw:	260mA @ 12V AC/DC 150mA @ 24V AC/DC
Static Strength:	1,500 Lbs.
Dynamic Strength:	70 Ft-Lbs.
Mode:	Selectable Fail safe / Fail-secure
Endurance:	1,000,000 Cycles (Factory Tested) 250,000 Cycles (UL Verified)
Operation:	AC - Buzz DC - Silent
Duty:	Continuous
Latch Monitor	SPDT, 100mA @ 24 VDC
Dimensions:	CX-ED1079: 3-3/8"H x 1-3/4"W x 1-7/32"D (86mm x 44mm x 31mm) CX-ED1079D: 3-3/8"H x 1-3/4"W x 1-3/8"D (86mm x 44mm x 35mm)