



# ELECTRIC STRIKES

## LOCKING PRODUCTS

### CX-EPD1289L SERIES: 3/4" 'UNIVERSAL' GRADE 1 FIRE RATED RIM STRIKES WITH PRELOAD

*CX-EPD1289L Series 3/4" Grade 1 electric RIM strikes for pullman latches offer the best strike quality, with a preload release function for superior performance under the most demanding conditions. Industry-leading preload strike design registered under U.S. Patent 10,988,959. The award-winning strikes are now also available in a unique all-black finish, including the jaws and latch monitor.*



| Features   |   |
|--|---|
| <ul style="list-style-type: none"> <li>Up to 15 lbs. of preload pressure</li> <li>3/4" latch projection</li> <li>'Plug-in' latch bolt monitor assembly</li> <li>'No-cut' surface mount</li> <li>Metal mounting jig included</li> </ul> | <ul style="list-style-type: none"> <li>Tamper resistant stainless steel construction</li> <li>Non-handed, with plug-in wiring harness</li> <li>Stainless steel cover plate included</li> <li>5 year warranty</li> </ul> |

### Specifications

|                             |   |
|-----------------------------|---|
| Voltage:                    | 12/24V, AC/DC   |
| Current Draw:               | 560mA @ 12VDC   280mA @ 24VDC                                     |
| Strength - Static:          | 1,500 lbs.   Dynamic: 70 Ft- lbs.                                 |
| Preload (Fail-Secure Only): | 15 lbs.   |
| Endurance:                  | 1,000,000 cycles (Factory Tested)<br>250,000 cycles (UL verified) |
| Mode:                       | Fail-safe / Fail-secure   Duty: Continuous                        |
| Fire Rating:                | UL 10C/CAN4-S104   3 hrs. (Fail Secure)                           |
| Mechanical Adjustment:      | Strike Body   |
| Operation:                  | AC-Buzz, DC-Silent  |
| Latch Projection:           | 3/4"  |
| Latch Bolt Monitor:         | SPDT, 100mA @ 24 VDC  |
| Dimensions (Body):          | 9-3/16"H x 1-7/8"W x 3/4" D<br>(233mm x 48mm x 19.8mm)            |

| MODELS         |   | List Price |
|----------------|---|------------|
| CX-EPD1289L    | 3/4" Surface mount Grade 1 RIM strike with preload, 12/24V, AC/DC, fail safe / fail secure, w/ 'plug-in' latch monitor assembly and metal mounting jig              | \$675.00   |
| CX-EPD1289L-BK | All-black finish, surface mount Grade 1 RIM strike with preload, 12/24V, AC/DC, fail safe / fail secure, w/ 'plug-in' latch monitor assembly and metal mounting jig | \$725.00   |

| SPACER PLATE   |  | List Price |
|----------------|--|------------|
| CX-EPD1289-SPC | 1/8" Spacer plate for CX-EPD1289L surface mount RIM strike | \$30.00    |

### CX-EPD1299L SERIES: 1/2" SURFACE MOUNT RIM STRIKES WITH PRELOAD

*CX-EPD1299L Series 1/2" Grade 1 electric RIM strikes for pullman latches offer the best strike quality, with a preload release function for superior performance under the most demanding conditions. Industry-leading preload strike design registered under U.S. Patent 10,988,959.*



| Features  |  |
|---|--|
| <ul style="list-style-type: none"> <li>'Universal' design, UL Security Listed</li> <li>1/2" latch projection</li> <li>2 Spacer plates included: 1/8" and 1/4"</li> <li>Stainless steel or all-black finish</li> </ul> | <ul style="list-style-type: none"> <li>Up to 15 lbs. of preload pressure on strike keepers</li> <li>Plug-in latch bolt monitor assembly included</li> <li>5 year warranty</li> </ul> |

### Specifications

|                             |   |
|-----------------------------|---|
| Voltage:                    | 12/24V, AC/DC   |
| Current Draw:               | 560mA @ 12VDC   280mA @ 24VDC                                     |
| Strength - Static:          | 1,500 lbs.   Dynamic: 70 Ft- lbs.                                 |
| Preload (Fail-Secure Only): | 15 Lbs.   |
| Endurance:                  | 1,000,000 cycles (Factory Tested)<br>250,000 cycles (UL verified) |
| Mode:                       | Fail-safe / Fail-secure   Duty: Continuous                        |
| Mechanical Adjustment:      | Strike Body   |
| Operation:                  | AC-Buzz, DC-Silent  |
| Latch Projection:           | 1/2"  |
| Latch Bolt Monitor:         | SPDT, 100mA @ 24 VDC  |
| Dimensions (Body):          | 9-3/16"H x 1-7/8"W x 1/2" D<br>(233mm x 48mm x 12.7mm)            |

| MODELS         |   | List Price |
|----------------|---|------------|
| CX-EPD1299L    | 1/2" Surface mount Grade 1 RIM, brushed aluminum finish strike with preload, 12/24V, AC/DC, fail safe/fail secure, w/ 'plug-in' latch monitor assembly & metal mounting jig | \$725.00   |
| CX-EPD1299L-BK | 1/2" Surface mount Grade 1 RIM strike, all-black finish, w/ preload, 12/24V, AC/DC, fail safe/fail secure, w/ 'plug-in' latch monitor assembly & metal mounting jig         | \$760.00   |