

CV-550SPK

STAND-ALONE PROX READER AND KEYPAD



CV-550SPK

FEATURES

- UP TO 2,000 USERS – CARDS OR TAGS
- BATCH CARD/TAG ENROLLMENT
- CAST METAL HEAVY DUTY CONSTRUCTION
- BACKLIT VANDAL RESISTANT KEYPAD
- WEATHER RESISTANT IP65 RATED
- SUPPORTS CARD, PIN, CARD + PIN (HID 26, 37 BIT FORMAT)
- 4 TO 8 DIGIT PIN CODE LENGTH
- (1) FORM 'C' RELAY OUTPUT
- TAMPER ALARM OUTPUT
- REQUEST TO EXIT DEVICE INPUT
- DOOR CONTACT INPUT
- ADJUSTABLE DOOR ALARM TIME AND DOOR OPEN TIME
- WIEGAND 26 BIT INPUT AND OUTPUT
- 3 YEAR WARRANTY

DESCRIPTION

Camden CV-550SPK stand-alone, HID format, prox reader and keypad supports up to 2000 users with card, PIN, or card and PIN access. It features a cast metal housing and backlit keypad with fully potted electronics, making CV-550SPK both weather (IP65 rated) and vandal resistant. In addition, the CV-550SPK has inputs for REX switch/sensor, door contacts, as well as Form 'C' relay, tamper and Wiegand 26 bit outputs. User prox cards or tags can easily be individually or batch enrolled.


APPLICATION

Camden CV-550SPK offers a complete 1 door access control solution for high traffic indoor or outdoor applications that demand weather and vandal resistant performance over years of operation. The 26 bit Wiegand input and output allows the unit to also operate as a dual credential (prox reader and keypad) access control system device. CV-550SPK is ideal for professional offices, healthcare, schools, retail stores, commercial and industrial applications. CV-550SPK may be used to control entry or egress through electrically locked doors or for activating/deactivating overhead doors, automatic doors, elevators, equipment or machinery.

PROXIMITY READER

SPECIFICATIONS

OPERATING VOLTAGE:	12/24VDC, 12/18VAC
USER CAPACITY:	2,000
CARD TYPE:	HID FORMAT, 26 AND 37 BIT
READ RANGE:	1" TO 2 1/2" (2.5 CM TO 6.3 CM)
CURRENT DRAW:	80MA
CONTACT TYPE:	1 FORM 'C'
CONTACT RATING:	2A
ALARM OUTPUT:	20MA
WEATHER RESISTANCE:	IP65
DOOR RELAY TIME:	0 TO 99 SECONDS
ALARM TIME:	0 TO 3 MINUTES
WIEGAND INTERFACE:	26 BIT
OPERATING TEMPERATURE:	-4°F TO 140°F (-20°C TO 60°C)
DIMENSIONS:	5" H x 3 1/4" W x 1 1/8"D (128mm x 82mm x 28mm)
WEIGHT:	1.5 LBS. (700 G)



CV-550SPK

ORDER INFORMATION

CV-550SPK:	STAND-ALONE PROX READER & KEYPAD, 1 RELAY, 2000 USERS
------------	---

OPTIONS

COMPATIBLE READERS & CARDS

CV-CSH:	HID FORMAT ISO PROX. CARD, PACKAGE OF 10
CV-CSH-B:	HID FORMAT ISO PROX. CARD, PACKAGE OF 100
CV-KTH:	HID FORMAT ISO PROX TAG, PACKAGE OF 10
CV-KTH-B:	HID FORMAT ISO PROX TAG, PACKAGE OF 100
CV-7400:	HID (DUAL) FORMAT READER