



ELECTRIC STRIKES

LOCKING PRODUCTS

CX-EPD1289L SERIES: 3/4" SURFACE MOUNT FIRE RATED RIM STRIKES WITH PRELOAD

CX-EPD1289L Series 3/4" Grade 1 electric RIM strikes for pullman latches offer the best strike quality, with a preload release function for superior performance under the most demanding conditions. Industry-leading preload strike design registered under U.S. Patent 10,988,959. These award-winning strikes are now also available in a unique all-black finish, including the jaws and latch monitor.



UL10C/
CAN4-S104,
3hr. Fire rating



UL 1034
UL 294



Features

- Up to 15 lbs of preload pressure
- 3/4" latch projection
- 'Plug-in' latch bolt monitor included
- 'No-cut' surface mount
- Metal mounting jig included
- Tamper resistant stainless steel construction
- Non-handed, with plug-in wiring harness
- Stainless steel cover plate included
- ANSI/BHMA A156.31, Grade 1 certified
- 5 year warranty

Specifications

Voltage:	12/24V, AC/DC
Current Draw:	560mA @ 12 VDC 280mA @ 24 VDC
Strength - Static:	1,500 lbs Dynamic: 70 Ft- lbs
Preload (Fail-Secure Only):	15 lbs
Endurance:	1,000,000 cycles (Factory Tested) 500,000 cycles (UL verified)
Mode:	Fail-safe/Fail-secure Duty: Continuous
Fire Rating:	UL 10C/CAN4-S104 3 hrs. (Fail Secure)
Mechanical Adjustment:	Strike Body
Operation:	AC- Buzz, DC - Silent
Latch Projection:	3/4"
Latch Bolt Monitor:	SPDT, 100mA @ 24 VDC
Dimensions:	CX-EPD1289L: 9-3/16"H x 1-15/16"W x 3/4"D (233mm x 49mm x 20mm) CX-RIM-SB: 9-3/16"H x 1-31/32"W x 1-1/4"D (233mm x 50mm x 32mm)

MODELS

List Price

CX-EPD1289L	3/4" Surface mount Grade 1 RIM strike with preload, 12/24V, AC/DC, fail safe/fail secure, w/ 'plug-in' latch monitor assembly and metal mounting jig	\$575.00
CX-EPD1289L-BK	All-black finish, surface mount Grade 1 RIM strike with preload, 12/24V, AC/DC, fail safe/fail secure, w/ 'plug-in' latch monitor assembly and metal mounting jig	\$650.00

SPACER PLATE

CX-EPD1289-SPC	1/8" Spacer plate for CX-EPD1289L surface mount RIM strike	\$25.00
----------------	--	---------

FILLER PLATE

60-35E014	RIM Strike Filler Plate for use with Hager and SDC exit devices	\$22.00
-----------	---	---------

SURFACE MOUNTING BOX

CX-RIM-SB	Aluminum surface mounted adapter box for mounting CX-EPD1289L on the inactive leaf of a double door	\$80.00
CX-RIM-SB-BK	Aluminum surface mounted adapter box for mounting CX-EPD1289L on the inactive leaf of a double door, all black finish	\$95.00

NEW



CX-EPD1289-SPC

CX-RIM-SB

60-35E014



CX-EPD1299L SERIES: 1/2" SURFACE MOUNT RIM STRIKES WITH PRELOAD

CX-EPD1299L Series 1/2" Grade 1 electric RIM strikes for pullman latches offer the best strike quality, with a preload release function for superior performance under the most demanding conditions. Industry-leading preload strike design registered under U.S. Patent 10,988,959.

UL 1034
UL 294

Features

- 'Universal' design, UL Security Listed
- 1/2" latch projection
- 2 Spacer plates included: 1/8" and 1/4"
- Stainless steel or all-black finish
- Up to 15 lbs of preload pressure on strike keepers
- Plug-in latch bolt monitor assembly included
- ANSI/BHMA A156.31, Grade 1 certified
- 5 year warranty

MODELS

List Price

CX-EPD1299L	1/2" Surface mount Grade 1 RIM, brushed aluminum finish strike with preload, 12/24V, AC/DC, fail safe/fail secure, w/ 'plug-in' latch monitor assembly & metal mounting jig	\$610.00
CX-EPD1299L-BK	1/2" Surface mount Grade 1 RIM strike, all-black finish, w/ preload, 12/24V, AC/DC, fail safe/fail secure, w/ 'plug-in' latch monitor assembly & metal mounting jig	\$700.00

SPACER PLATE

60-35E013	1/8" Spacer plate for CX-EPD1299L surface mount RIM strike	\$25.00
60-35E015	1/4" Spacer plate for CX-EPD1299L surface mount RIM strike	\$35.00
60-35E013-BK	1/8" Spacer plate for CX-EPD1299L surface mount RIM strike, All-black finish	\$25.00
60-35E015-BK	1/4" Spacer plate for CX-EPD1299L surface mount RIM strike, All-black finish	\$35.00

FILLER PLATE

60-35E014	RIM Strike filler plate for use with Hager and SDC exit devices	\$22.00
-----------	---	---------

SURFACE MOUNTING BOX

CX-RIM-SB	Aluminum surface mounted adapter box for mounting CX-EPD1299L on the inactive leaf of a double door	\$80.00
CX-RIM-SB-BK	Aluminum surface mounted adapter box for mounting CX-EPD1299L on the inactive leaf of a double door, all black finish	\$95.00

NEW

Specifications

Voltage:	12/24V, AC/DC
Current Draw:	560mA @ 12VDC 280mA @ 24VDC
Strength - Static:	1,500 lbs Dynamic: 70 Ft-lbs
Preload (Fail-Secure Only):	15 lbs
Endurance:	1,000,000 cycles (Factory Tested) 500,000 cycles (UL verified)
Mode:	Fail-safe/Fail-secure Duty: Continuous
Mechanical Adjustment:	Strike Body
Operation:	AC - Buzz, DC - Silent
Latch Projection:	1/2"
Latch Bolt Monitor:	SPDT, 100mA @ 24 VDC
Dimensions:	CX-EPD1299L: 9-3/16"H x 1-15/16"W x 9/16"D (233mm x 49mm x 14mm) CX-RIM-SB: 9-3/16"H x 1-31/32"W x 1-1/4"D (233mm x 50mm x 32mm)



CX-RIM-SB



60-35E014