



CX-DE1200 Series Delayed Egress Magnetic Lock



CX-DE1200 Series Single and Double Door delayed egress magnetic locks are designed to provide the best performance and value in healthcare, childcare, retail, and institutional applications.

The innovative human voice and LED count down timer offers immediate comprehension of status for building occupants and these rugged locks are available in a range of models, with factory default operation, to meet NFPA, BOCA and local AHJ requirements.



Features

- Single and double door models
- Nuisance Delay period 1 or 2 seconds
- LED time display countdown with voice annunciation
- Choice of sensor activation:
 - Door Motion
 - Door Exit Device with momentary N/O contact
 - Push Bar with momentary N/O contact
- Auto / manual start-up on power restore
- Vandal Resistant proximity trigger sensor
- Auto sensing power input with polarity protection
- Anti-Pass back / Auto Re-Lock
- Accessories: sounder, speaker and reset station



SPECIFICATIONS

VOLTAGE: 12/24 VDC +/- 10% (Auto Sensing)
 CURRENT DRAW: 600mA / 330mA
 DPS RATING: 40 VDC, 0.25A (max.)
 ATS RATING: 30 VAC / 42.4 VDC, 5A (Max.)
 LOCK STATUS RELAY RATING: 30 VDC, 2A
 ALARM OUTPUT RATING: 30 VDC, 2A (Max.)

BOND SENSOR RATING: **CX-DE1200:** 30 VDC, 2A (Max.)
 HOLDING FORCE: Up to 1,200 lbs. (544 kg.) (Factory tested)
 TEMPERATURE RANGE: 32°F - 131°F (0°C to 55°C)
DIMENSIONS:
 ARMATURE PLATE: 2-5/8"W x 11"H x 1"D (68mm x 280mm x 23.5mm)
 LOCK: 3"W x 11"H x 3"D (76mm x 280mm x 74.5mm)

ORDERING INFORMATION

Delayed Egress Maglocks

CX-DE1200
 Single Door



Models:

CX-DE1200-N1, CX-DE1200-N2, CX-DE1200-N3, CX-DE1200-N4,
 CX-DE1200-B1, CX-DE1200-B2, CX-DE1200-B3

CX-DE1220
 Double Door (Single & Tandem)



Models:

CX-DE1220-N1, CX-DE1220-N2, CX-DE1220-N3, CX-DE1220-N4,
 CX-DE1220-B1, CX-DE1220-B2, CX-DE1220-B3

Mounting Accessories

CX-DE1214-38
 3/8" Filler Plate

CX-DE1214-58
 5/8" Filler Plate


CX-DE1215
 1" x 1.5" Angle Bracket

CX-DE1216
 1.5" x 1.5" Angle Bracket


CX-DE1217
 2.0" Angle Bracket

System Accessories


CX-DE-502SO
 Remote Annunciator for
 both audio & visual distinction
 The stainless steel faceplate
 has a piezo and tri-colour LED




CX-DESPK
 Remote Speaker Station for
 both audio & visual distinction
 RGB LED displays 3 designated
 states and the 8-ohm speaker can
 provide audio messages remotely



CX-DESPK15
 External 15-watt Audio
 Speaker Station
 Optional Aura™ PCB
 feature displays 3 colors
 for designated states



DIMENSIONS



CAMDEN DOOR CONTROLS **Opening New Doors to Innovation, Quality and Support!**

5502 Timberlea Blvd. Mississauga, ON Canada L4W 2T7 • Toll Free: 1 877 226-3369 (CAMDEN9)
 Tel: (905) 366-3377 • Fax: (905) 366-3378 • E-mail: info@camdencontrols.com • www.camdencontrols.com

