DOOR ACTIVATION DEVICES

CM-SR Series Receiver and Transmitters





Ultra compact two button transmitters are built tough, with 100ft min. range (line of sight). A system kit is available, complete with (1) receiver and (2) two-button fobs.

• 2-year battery life and low battery indication

SPECIFICATIONS				
CM-SRX2 Relay Receiver		CV-WTX2 Two Button Fob		
Voltage: Frequency: Current Draw (Max): Relay: Operating Temp: Dimensions:	12V or 24V AC/DC 868.35Mhz. 80mA (1) SPST, normally open, 1st relay momentary, 2nd momentary or latching/bi-stable, SPST normally closed, 1A @ 30 VDC -4°F to 185°F (-20°C to +85°C) 2-17/32"W x 3-3/4"H x 2-7/32"D (64mm x 95mm x 56mm)	Voltage: Current Draw: Operating Temp: Dimensions:	3 VDC, CR2032 type battery 12mA -4°F to 131°F (-20°C to +55°C) 1-15/32"W x 2-5/32"H x 3/8"D (37mm x 55mm x 10mm)	

ORDERING INFORMATION		
CM-SRX2	2 channel 868 Mhz. wireless receiver	
CV-WTX2	Ultra compact two-button key fob	
CM-SRFM2 Secure wireless kit, includes (1) CM-SRX2 wireless receiver and (2) CV-WTX2 two-button key fobs		



CAMDEN DOOR CONTROLS Opening New Doors to Innovation, Quality, and Support!



2395 Skymark Ave, Mississauga, ON Canada L4W 4Y6 • Toll Free: 1(877) 226-3369 (CAMDEN9) Tel: (905) 366-3377 | Fax: (905) 366-3378 | E-mail: info@camdencontrols.com | www.camdencontrols.com

Part #: MKTG-LIT-SP-CM-SRSERIES_R3