DOOR ACTIVATION DEVICES

CM-9600 / 9610 SERIES: ILLUMINATED PIEZO ELECTRIC PUSH / EXIT SWITCHES



CM-9600 and CM-9610 Series flush mount illuminated piezo push switches offer high visibility and weather/vandal resistance. The units feature a heavy duty stainless steel faceplate and an adjustable 40 second timer.

CM-9600 is single gang width (2-3/4") and CM-9610 is only 1-3/4" wide, perfect for door frames or narrow areas. The large 1" round diameter button is easy to activate with a light tap. Illumination and power relay is 12 to 24 VDC.

Switch illumination is jumper selectable and may be set for On, Off, Green to Red, Red to Green or non-lit operation. Field selectable for N/O or N/C output, and fail safe/fail secure operation.

Features

- · Rugged stainless steel face plate
- Red and/or green illumination
- Fail safe/non fail safe selectable
- N/O & N/C outputs

 Integrated adjustable 40 second timer · Optional cable for remote activation Lifetime 'Camden Tough' warranty with '2 for 1' replacement

SINGLE GA	SINGLE GANG FACEPLATE		
CM-9600	Illuminated piezo electric push button, blank faceplate	\$175.00	
NARROW	NARROW / JAMB FACEPLATE		

Remote Activation / Control		List Price
CM-9600C	Cable for remote activation / control of switch LED	\$28.00





CM-9600/7

CM-9610/3

Specifications

Voltage:	12/24 VDC
Contact Rating:	2A @ 30 VDC
Contact Type:	1 x N/C, 1 x N/O
Time Delay:	1 - 40 seconds
Temp Range:	-40°F to +180°F (-40°C to +82°C)
Std. Finish:	US32/C32D
Dimensions:	Single Gang: 4-1/2"H x 2-3/4"W x 1-1/2"D (114mm x 70mm x 38mm)
	Narrow / Jamb: 4-1/2"H x 1-3/4"W x 1-1/2"D (114mm x 45mm x 38mm)