


## CX-94S-12LS

1200 LBS. SURFACE MOUNT GATE LOCK



CX-94S-12LS

### FEATURES

- 1,200LBS HOLDING FORCE
- COMPATIBLE WITH ALL ACCESS/EGRESS SYSTEMS
- FIELD SELECTABLE 12/24V DC OPERATION
- CONDUIT FITTING FOR WEATHER RESISTANT INSTALLATION
- BUILT-IN LOCK SENSOR AND RELAY
- LIFETIME WARRANTY

### DESCRIPTION

Camden **CX-94S-12LS** gate locks are rugged magnetic locks designed for outdoor applications. They offer exceptional performance and value with ultra low current draw, making them the ideal choice for most gating projects.

### SPECIFICATIONS

VOLTAGE:	12/24V DC
CURRENT DRAW:	500MA@12V DC 250MA@24V DC
TEMP RANGE:	5F TO 122F (-15C TO 50C)
CONTACT RATING:	BOND SENSOR: 1A@30V DC
DIMENSIONS (BODY):	8"H x 2 1/2"W x 1 5/8"D (203mm x 63mm x 41.5mm)

### ORDERING INFORMATION

MODEL	DESCRIPTION
CX-94S-12LS	1200 LBS. SURFACE MOUNT GATE LOCK WITH LOCK SENSOR AND RELAY

ELECTRIC STRIKES

CABINET LOCKS

MAGNETIC LOCKS

DOOR ALARMS

RELAYS & TIMERS

POWER SUPPLIES

TRANSFORMERS

ANNUNCIATORS

RESTROOM CONTROL KITS