



CX-ED1579L

**‘ALL IN ONE’ FIRE RATED
ELECTRIC STRIKE**

STANDARD FEATURES	CAMDEN 1579L	HES1006	HES1500	HES1600	RCI F2164	VON DUPRIN 8400	VON DUPRIN 6210
Accommodate both Cylindrical and Mortise Locksets	√	√	√	√	√	√	√
Accommodate all brands of Mortise Locksets	√	√	√	√	√	√	√
Accommodate Deadbolts	√	√	√	√	√	√	X
Release and capture deadbolts	X	√	X	X	X	X	X
Strike body depth	1-5/8"	1-11/16"	1-3/8"	1-5/8"	1-5/8"	1-5/8"	1-5/8"
Strike cavity	3-1/4"	3-1/4"	3-1/4"	3-1/4"	3-1/4"	3-1/4"	3-1/4"
Stainless steel construction	√	√	√	√	√	√	√
Static strength (Lbs.)	1800	3700	1500	1500	1500	1500	1500
Dynamic strength	70	350	70	70	70	70	70
Endurance-Cycles	2M	1M	1M	1M	2M	2M	1M
Field Selectable Fail Safe-Fail Secure	√	X	X	X	√	√	X
Non handed	√	√	√	√	√	√	√
Easy install shims to improve locking	√	X	X	X	X	X	X
Horizontal Adjustmnet	Y- Shims Required	Y- Shims Required	√	√	Y- Shims Required	Y- Shims Required	Y- Shims Required
Plug in connectors	√	√	√	√	√	√	√
Trim Plate for keepers included	√	√	√	√	√	√	X
Lip extension	X	√	√	√	X	X	X
Latch bolt monitor	Standard	Cost Option	Cost Option	Cost Option	Cost Option	Cost Option	Cost Option
Install template/jig	√	√	√	√	X	X	X
Frame types	All	All	All	All	All	All	All
UL-10C 3 Hour Fire rated	√	√	√	√	√	√	√
UL-1034 Burglary listed	√	√	√	√	√	√	√
Dual voltage 12-24	√	√	√	√	√	√	X
AC/DC	√	X	X	X	√	√	X
Continuous duty	√	√	√	√	√	√	√
POE friendly	√	X	√	√	√	√	X
Warranty	5 Years	5 Years	5 Years	5 Years	5 Years	5 Years	5 years

Note: Specifications are subject to change without notice..... FEBRUARY 5, 2018