

ALL-ACTIVE SWITCHES



CM-2510 & CM-2520 SERIES: VESTIBULE AND COMBO KEY SWITCHES

CM-2510 and CM-2520 push plate switches have a 4 1/2" square faceplate with a 2" x 4" switch, designed for easy installation directly on a double gang electric box. The tubular switches provide virtually silent operation. CM-2510 includes a SPST maintained switch. Mortise cylinder and keys are sold separately.

Features

- Heavy Duty Stainless steel
- 2" x 4" (50mm x 101mm) push plate conforms to new OBC requirements
- · Minimal actuation force
- Key switch easily enables/disables push plate switch
- 3 year 'Camden Tough' warranty with '2 for 1' replacement

MODELS		List Price
CM-2510	Double Gang Push Plate/Key Switch	\$170.00
CM-2520	Double Gang Vestibule Push Plate Switch, with /4AL, /4AR Graphics	\$174.00

OPTIONS: (Add suffix and cost to model above)

FACEPLATE GR	RAPHIC OPTIO	NS	
	ف	PUSH TO OPEN	POUSSEZ POUR OUVRIR
CM-xx/1 \$00.00	CM-xx/2 \$10.00	CM-xx/3 \$10.00	CM-xx/3F \$10.00
PUSH TO OPEN	POUSSEZ POUR OUVRIR	PUSH PUSH TO TO OPEN LOCK	
CM-xx/4 \$10.00	CM-xx/4F \$60.00	CM-xx/48 \$14.00	

NOTE: /2, /4, /4F: Blue and /3, /3F: Black. /48 Wheelchair/Push to Open in Blue, Lock Symbol/Push to Lock in Red

MORTISE CYLINDERS		List Price
CM-1000/60KA	Mortise cylinder 1 1/8", solid brass chrome finish, keyed alike	\$30.00
CM-1000/60KD	Mortise cylinder as above, keyed different	\$30.00

WATER PROOF OPTION		List Price
CM-xxx-WT	Add 'WT' to product # for boot and water tight coating	\$60.00





Specifications

Voltage:	12/24V AC/DC
Contact Type:	Push Plate: N/O SPST, Momentary Key Switch: N/O SPST Maintained
Contact Rating:	Push Plate: 3A@30V DC Key Switch: 6A@30V DC
Temp Range:	-40°F to 140°F (-40°C to +60°C)
Std. Finish:	US32 / C32D
Dimensions:	CM-2510: 4 1/2"H x 4 1/2"W x 1 3/4"D (114mm x 114mm x 44mm) CM-2520: 4 1/2"H x 4 1/2"W x 1 3/16"D (114mm x 114mm x 30mm)





CM-2510/3

CM-2520/4



CM-2520/48