


LOCKING PRODUCTS

CX-ED1579L: 'ALL IN ONE' GRADE 1 FIRE RATED ELECTRIC STRIKE









Features

- · For mortise and cylindrical locksets
- 3/4" (19mm) latch projection (throw)
- · Selectable fail safe/fail secure operation
- Selectable 12/24V AC/DC
- · 6 Stainless Steel faceplates included
- Non-handed, LH/RH
- · Easy fit connectors for power & monitoring wires
- · Latch monitoring
- · Stainless steel strike body
- · 5 year warranty

	<u>'</u>		
MODELS		List Price	
CX-ED1579L	Grade 1 'All In One' Fire Rated Strike, 12/24V AC/DC, for mortise & cylindrical locksets, c/w 6 stainless steel faceplates	\$650.00	
CX-ED1579L-BK	Grade 1 'All In One' Fire Rated Strike, 12/24V AC/DC, for mortise & cylindrical locksets c/w 6 black faceplates	\$722.00	
FACEPLATES			
Stainless Steel Finish (BHMA 630, US32D)			
CX-EMP-1	Stainless steel faceplate for Sargent, Schlage & Yale Mortise Locksets	\$23.00	
CX-EMP-2	Stainless steel faceplate for Arrow, Corbin, & Best mortise locksets	\$23.00	
CX-EMP-3	Stainless steel faceplate for centerline mortise or cylindrical locksets	\$23.00	
CX-EMP-4	Stainless steel faceplate for mortise locksets with deadbolt	\$27.00	
CX-EMP-5	Stainless steel faceplate for all mortise locks that include both latch & deadbolt	\$27.00	
CX-EMP-6	Stainless steel faceplate for Sargent 8100/7700, Schlage & Yale 8700	\$27.00	
Black Finish (BHMA 622, US19)			
CX-EMP-1-BK	Black faceplate for Sargent, Schlage & Yale Mortise Locksets	\$35.00	
CX-EMP-2-BK	Black faceplate for Arrow, Corbin, & Best mortise locksets	\$35.00	
CX-EMP-3-BK	Black faceplate for centerline mortise or cylindrical locksets	\$35.00	
CX-EMP-4-BK	Black faceplate for mortise locksets with deadbolt	\$49.00	
CX-EMP-5-BK	Black faceplate for all mortise locks that include both latch & deadbolt	\$49.00	
CX-EMP-6-BK	Black faceplate for Sargent 8100/7700, Schlage & Yale 8700	\$49.00	



Specifications

	······································
Voltage:	12/24V AC/DC
Current Draw:	260mA @ 12V AC/DC
	150mA @ 24V AC/DC
Static Force:	1,500 Lbs.
Dynamic Force:	70 Ft- Lbs.
Mode:	Fail-safe/Fail-secure
	Field selectable
Operation:	AC - Buzz
	DC - Silent
Duty:	Continuous (DC)
Mounting:	Non-Handed
Endurance:	1,500,000 Cycles (Factory Tested)
	250,000 Cycles (UL Verified)
Fire Rating:	UL10C / CAN4-S104
	3 hrs. (Fail Safe)
Latch Bolt Monitor:	SPDT, 100mA @ 24V DC
Dimensions:	Body:
	4-7/8"H x 1-1/4"W x-1 3/4"D
	(124mm x 32mm x 45mm)

Stainless Steel Faceplates







CX-EMP-4





CX-EMP-6