



ELECTRIC STRIKES

LOCKING PRODUCTS

CX-EPD1289L SERIES: 3/4" SURFACE MOUNT FIRE RATED RIM STRIKES WITH PRELOAD

CX-EPD1289L Series 3/4" Grade 1 electric RIM strikes for pullman latches offer the best strike quality, with a preload release function for superior performance under the most demanding conditions. Industry-leading preload strike design registered under U.S. Patent 10,988,959. These award-winning strikes are now also available in a unique all-black finish, including the jaws and latch monitor.



UL10C/
CAN4-S104,
3hr. Fire rating



UL 1034
UL 294



Features

- Up to 15 lbs. of preload pressure
- 3/4" latch projection
- 'Plug-in' latch bolt monitor included
- 'No-cut' surface mount
- Metal mounting jig included
- Tamper resistant stainless steel construction
- Non-handed, with plug-in wiring harness
- Stainless steel cover plate included
- 5 year warranty

Specifications

Voltage: 12/24V, AC/DC
Current Draw: 560mA @ 12 VDC | 280mA @ 24 VDC
Strength - Static: 1,500 lbs. | Dynamic: 70 Ft.-lbs.
Preload (Fail-Secure Only): 15 lbs.
Endurance: 1,000,000 cycles (Factory Tested)
250,000 cycles (UL verified)
Mode: Fail-safe / Fail-secure | Duty: Continuous
Fire Rating: UL 10C/CAN4-S104 | 3 hrs. (Fail Secure)
Mechanical Adjustment: Strike Body
Operation: AC-Buzz, DC-Silent
Latch Projection: 3/4"
Latch Bolt Monitor: SPDT, 100mA @ 24 VDC
Dimensions: **CX-EPD1289L:**
9-3/16"H x 1-15/16"W x 3/4"D
(233mm x 49mm x 20mm)
CX-RIM-SB:
9-3/16"H x 1-31/32"W x 1-1/4"D
(233mm x 50mm x 32mm)

MODELS

List Price

CX-EPD1289L	3/4" Surface mount Grade 1 RIM strike with preload, 12/24V, AC/DC, fail safe / fail secure, w/ 'plug-in' latch monitor assembly and metal mounting jig	\$550.00
CX-EPD1289L-BK	All-black finish, surface mount Grade 1 RIM strike with preload, 12/24V, AC/DC, fail safe / fail secure, w/ 'plug-in' latch monitor assembly and metal mounting jig	\$600.00

SPACER PLATE

CX-EPD1289-SPC	1/8" Spacer plate for CX-EPD1289L surface mount RIM strike	\$20.00
----------------	--	---------

FILLER PLATE

60-35E014	RIM Strike Filler Plate for use with Hager and SDC Exit Devices	\$22.00
-----------	---	---------

SURFACE MOUNTING BOX

CX-RIM-SB	Aluminum surface mounted adapter box for mounting EPD-1289L (or 1299L) on a double door	\$55.00
-----------	---	---------



CX-EPD1289-SPC



CX-RIM-SB



60-35E014



CX-EPD1299L SERIES: 1/2" SURFACE MOUNT RIM STRIKES WITH PRELOAD

CX-EPD1299L Series 1/2" Grade 1 electric RIM strikes for pullman latches offer the best strike quality, with a preload release function for superior performance under the most demanding conditions. Industry-leading preload strike design registered under U.S. Patent 10,988,959.

Features

- 'Universal' design, UL Security Listed
- 1/2" latch projection
- 2 Spacer plates included: 1/8" and 1/4"
- Stainless steel or all-black finish
- Up to 15 lbs. of preload pressure on strike keepers
- Plug-in latch bolt monitor assembly included
- 5 year warranty

MODELS

List Price

CX-EPD1299L	1/2" Surface mount Grade 1 RIM, brushed aluminum finish strike with preload, 12/24V, AC/DC, fail safe/fail secure, w/ 'plug-in' latch monitor assembly & metal mounting jig	\$575.00
CX-EPD1299L-BK	1/2" Surface mount Grade 1 RIM strike, all-black finish, w/ preload, 12/24V, AC/DC, fail safe/fail secure, w/ 'plug-in' latch monitor assembly & metal mounting jig	\$625.00
FILLER PLATE		
60-35E014	RIM Strike Filler Plate for use with Hager and SDC Exit Devices	\$22.00
SURFACE MOUNTING BOX		
CX-RIM-SB	Aluminum surface mounted adapter box for mounting EPD-1289L (or 1299L) on a double door	\$55.00

UL 1034
UL 294

Specifications

Voltage:	12/24V, AC/DC
Current Draw:	560mA @ 12VDC 280mA @ 24VDC
Strength - Static:	1,500 lbs. Dynamic: 70 Ft- lbs.
Preload (Fail-Secure Only):	15 Lbs.
Endurance:	1,000,000 cycles (Factory Tested) 250,000 cycles (UL verified)
Mode:	Fail-safe / Fail-secure Duty: Continuous
Mechanical Adjustment:	Strike Body
Operation:	AC - Buzz, DC - Silent
Latch Projection:	1/2"
Latch Bolt Monitor:	SPDT, 100mA @ 24 VDC
Dimensions:	CX-EPD1299L: 9-3/16"H x 1-15/16"W x 9/16" D (233mm x 49mm x 14mm) CX-RIM-SB: 9-3/16"H x 1-31/32"W x 1-1/4"D (233mm x 50mm x 32mm)



CX-RIM-SB



60-35E014