



CX-ED1379/CX-ED1309: 'UNIVERSAL' GRADE 1 STRIKES FOR NARROW STILE ALUMINUM FRAME

CX-ED1309 Grade 1 electric strikes for cylindrical and spring latch locksets offer 'Universal' performance, the best strike quality and features, including field selectable voltage and fail safe/fail secure operation with a wide range of aluminum and dark bronze faceplates.



UL 1034
UL 294



Features

- Ideal for cylindrical and spring latch locksets in wood, hollow metal or aluminum frames
- 1/2" to 5/8" (12mm to 16mm) latch projection
- Selectable fail safe/fail secure operation
- 1-3/4" (44.5 mm) minimum door thickness
- Selectable 12/24V AC/DC
- Wide range of aluminum and dark bronze faceplates
- Radius faceplate available for use on double doors
- Easy fit connectors and mounting tabs included
- BHMA certified A156.31
- 5 year warranty

MODELS

List Price

CX-ED1379	Grade 1 'Universal' Electric Strike, 12/24V AC/DC, fail safe/fail secure operation, includes: (1) CX-ESF-2 ANSI Round Faceplate - Brushed Aluminum finish (1) CX-ESF-2BZ ANSI Round Faceplate - Dark Bronze finish	\$220.00
CX-ED1309	Grade 1 'Universal' Electric Strike Body, 12/24V AC/DC, fail safe/fail secure operation. Order faceplate separately.	\$200.00

FACEPLATES

List Price

Brushed Aluminum Finish (BHMA 628)

CX-ESF-1	ANSI Square faceplate for CX-ED1309, Brushed aluminum finish	\$13.00
CX-ESF-2	ANSI Round faceplate for CX-ED1309, Brushed aluminum finish	\$13.00
CX-ESF-2BR	Radius ANSI round faceplate for CX-ED1309, Brushed aluminum finish	\$23.00
CX-ESF-3	Hollow metal faceplate for CX-ED1309, Brushed aluminum finish	\$13.00
CX-ESF-3BR	Radius hollow metal faceplate for CX-ED1309, Brushed aluminum finish	\$23.00
CX-ESF-4	Wood frame faceplate for CX-ED1309, Brushed aluminum finish	\$13.00

Dark Bronze Finish (BHMA 710)

CX-ESF-1BZ	ANSI Square faceplate for CX-ED1309, Dark bronze finish	\$13.00
CX-ESF-2BZ	ANSI Round faceplate for CX-ED1309, Dark bronze finish	\$13.00
CX-ESF-2BR-BZ	Radius ANSI round faceplate for CX-ED1309, Dark bronze finish	\$23.00
CX-ESF-3BZ	Hollow metal faceplate for CX-ED1309, Dark bronze finish	\$13.00
CX-ESF-3BR-BZ	Radius hollow metal faceplate for CX-ED1309, Dark bronze finish	\$23.00
CX-ESF-4BZ	Wood frame faceplate for CX-ED1309, Dark bronze finish	\$13.00

Specifications

Voltage:	12/24V AC/DC
Current Draw:	260mA @ 12V AC/DC 150mA @ 24V AC/DC
Faceplates:	CX-ED1379: Brushed aluminum (BHMA628) Dark bronze (BHMA 710)
Static Strength:	1,500 lbs.
Dynamic Strength:	70 Ft. lbs.
Mode:	Fail-safe/Fail-secure Field selectable
Operation:	AC - Buzz DC - Silent
Duty:	Continuous (DC)
Endurance:	1,000,000 Cycles (Factory Tested) 500,000 Cycles (UL Verified)
Dimensions:	Body: 4-7/8" H x 1-11/16" W x 1-5/8" D (124mm x 43mm x 42mm)