



CX-ED2071/CX-ED2079: 'UNIVERSAL' LOW PROFILE GRADE 2 ELECTRIC STRIKES

CX-ED2071 low profile grade 2 ANSI electric strike for cylindrical locksets provides exceptional value for installations that require 8-16V AC/DC operation. It includes 3 faceplates, selectable fail safe/fail secure operation and horizontal adjustment of the strike body.

CX-ED2079 low profile 'Universal' grade 2 ANSI electric strike for cylindrical locksets provides exceptional value with 3 faceplates, and selectable 12/24V AC/DC voltage, fail safe/fail secure operation and horizontal adjustment of the strike body.

CX-ED2079-1 Low profile 'Universal' grade 2 ANSI strike for cylindrical locksets, with (1) ANSI square faceplate, provides the best strike value.



BHMA
CERTIFIED



CX-ED2071/
CX-ED2079

Features

- Centerline latch entry for cylindrical locksets, 1/2" to 5/8" latch projection
- Horizontal adjustability of strike body
- Low profile strike body
- Selectable fail safe/fail secure
- BHMA certified A156.31 (CX-ED2079 Series)
- 5 year warranty
- CX-ED2079: 12/24V strike, includes (3) stainless steel faceplates: ANSI square, hollow metal door and wood door
- CX-ED2079-1: 12/24V strike, includes (1) stainless steel ANSI square faceplate
- CX-ED2071: 8V – 16V strike, includes (3) stainless steel faceplates ANSI square, hollow metal door, and wood door

MODELS

		List Price
CX-ED2071	'Universal' electric strike, 8 - 16V AC/DC, fail safe/fail secure operation, horizontal adjustment, w/ 3 stainless steel faceplates (CX-ESP1B, ESP3B & ESP4B)	\$215.00
CX-ED2079*	'Universal' electric strike, 12/24V AC/DC, fail safe/fail secure operation, horizontal adjustment, w/ 3 stainless steel faceplates (CX-ESP1B, ESP3B & ESP4B)	\$205.00
CX-ED2079-1*	'Universal' electric strike, 12/24V AC/DC, fail safe/fail secure operation, horizontal adjustment, w/ 1 stainless steel faceplate (EX-ESP1B)	\$185.00
CX-ED2071-BK	'Universal' electric strike, 8 - 16V AC/DC, fail safe/fail secure operation, horizontal adjustment, w/ 3 black faceplates (CX-ESP1B-BK, ESP3B-BK & ESP4B-BK)	\$226.00
CX-ED2079-BK*	'Universal' electric strike, 12/24V AC/DC, fail safe/fail secure operation, horizontal adjustment, w/ 3 black faceplates (CX-ESP1B-BK, ESP3B-BK & ESP4B-BK)	\$226.00
CX-ED2079-1-BK*	'Universal' electric strike, 12/24V AC/DC, fail safe/fail secure operation, horizontal adjustment, w/ 1 black faceplate (EX-ESP1B-BK)	\$211.00

FACEPLATES

		List Price
Included In Package		
CX-ESP1B	ANSI Square, 4-7/8" x 1-1/4", stainless steel	\$20.00
CX-ESP3B	Hollow Metal Door, 6-7/8" x 1-1/4", stainless steel	\$22.00
CX-ESP4B	Wood Door, 7-15/16" x 1-7/16", stainless steel	\$24.00

Optional Faceplates

CX-ESP2B	ANSI Round, 4-7/8" x 1-1/4", stainless steel	\$20.00
CX-ESP1B-BK	ANSI Square, 4-7/8" x 1-1/4", all-black finish (BHMA 622, US19)	\$42.00
CX-ESP2B-BK	ANSI Round, 4-7/8" x 1-1/4", all-black finish (BHMA 622, US19)	\$42.00
CX-ESP3B-BK	Hollow Metal Door, 6-7/8" x 1-1/4", all-black finish (BHMA 622, US19)	\$42.00
CX-ESP4B-BK	Wood Door, 7-15/16" x 1-7/16", all-black finish (BHMA 622, US19)	\$42.00

LIP EXTENSION BRACKETS

		List Price
CX-ED-LIP1	1" Lip extension for ANSI strikes (Stackable)	\$24.00
CX-ED-LIP2	2" Lip extension for ANSI strikes	\$28.00

Specifications

Voltage:	CX-ED2071: 8 - 16V, AC/DC CX-ED2079: 12/24V, AC/DC
Current Draw:	CX-ED2071: 305mA @ 8 VDC, 625mA @ 16 VDC CX-ED2079: 190mA @ 8 VAC, 460mA @ 16 VAC
Static Strength:	1000 lbs.
Dynamic Strength:	50 Ft. lbs.
Mode:	Selectable fail safe/fail secure
Endurance:	CX-ED2071 & CX-ED2079: 700,000 cycles (Factory Tested) CX-ED2079: 500,000 cycles (UL Verified)
Operation:	AC – Buzz DC – Silent
Duty:	CX-ED2071: Intermittent CX-ED2079: Continuous
Mounting:	Non-handed
Dimensions (Body):	3-3/8"H x 1-7/8"W x 1-7/32"D (86mm x 44mm x 31mm)



CX-ESP1B CX-ESP3B CX-ESP4B