



CX-EPD1299L SERIES: 1/2" SURFACE MOUNT RIM STRIKES WITH PRELOAD

CX-EPD1299L Series 1/2" Grade 1 electric RIM strikes for pullman latches offer the best strike quality, with a preload release function for superior performance under the most demanding conditions. Industry-leading preload strike design registered under U.S. Patent 10,988,959.



Features

- 'Universal' design, UL Security Listed
- 1/2" latch projection
- 2 Spacer plates included: 1/8" and 1/4"
- Stainless steel or all-black finish
- Up to 15 lbs. of preload pressure on strike keepers
- Plug-in latch bolt monitor assembly included
- BHMA certified A156.31
- 5 year warranty

MODELS		List Price
CX-EPD1299L	1/2" Surface mount Grade 1 RIM, brushed aluminum finish strike with preload, 12/24V, AC/DC, fail safe/fail secure, w/ 'plug-in' latch monitor assembly & metal mounting jig	\$610.00
CX-EPD1299L-BK	1/2" Surface mount Grade 1 RIM strike, all-black finish, w/ preload, 12/24V, AC/DC, fail safe/fail secure, w/ 'plug-in' latch monitor assembly & metal mounting jig	\$700.00

SPACER PLATE

60-35E013	1/8" Spacer plate for CX-EPD1299L surface mount RIM strike	\$20.00
60-35E015	1/4" Spacer plate for CX-EPD1299L surface mount RIM strike	\$35.00
60-35E013-BK	1/8" Spacer plate for CX-EPD1299L surface mount RIM strike, All-black finish	\$20.00
60-35E015-BK	1/4" Spacer plate for CX-EPD1299L surface mount RIM strike, All-black finish	\$35.00

FILLER PLATE

60-35E014	RIM Strike filler plate for use with Hager and SDC exit devices	\$22.00
-----------	---	---------

SURFACE MOUNTING BOX

CX-RIM-SB	Aluminum surface mounted adapter box for mounting CX-EPD1289L (or 1299L) on a double door	\$80.00
-----------	---	---------

Specifications

Voltage:	12/24V, AC/DC
Current Draw:	560mA @ 12 VDC 280mA @ 24 VDC
Strength - Static:	1,500 lbs. Dynamic: 70 Ft-lbs.
Preload (Fail-Secure Only):	15 lbs.
Endurance:	1,000,000 cycles (Factory Tested) 500,000 cycles (UL verified)
Mode:	Fail-safe/Fail-secure Duty: Continuous
Mechanical Adjustment:	Strike Body
Operation:	AC-Buzz, DC-Silent
Latch Projection:	1/2"
Latch Bolt Monitor:	SPDT, 100mA @ 24 VDC
Dimensions:	CX-EPD1299L: 9-3/16"H x 1-15/16"W x 9/16"D (233mm x 49mm x 14mm) CX-RIM-SB: 9-3/16"H x 1-31/32"W x 1-1/4"D (233mm x 50mm x 32mm)



NEW!

CX-RIM-SB

60-35E014