



LOCKING PRODUCTS

CX-EPD0009: MAGNETIC CABINET LOCK

CX-EPD0009 Magnetic Cabinet Lock has an ultra-compact design and is an easily installed high-security lock for virtually any enclosure door, including computer cabinets, refrigerators, lockers, and retail display counters. This 12V or 24V magnetically operated lock has a holding force of 440 lbs. and is water-resistant, making it ideal for humid environments, including inside fridges and freezers.



Features	
<ul style="list-style-type: none"> • Front or side mounting for use with swing or sliding doors and drawers • Armature plate adjusts to door alignment • 5 lbs. preload 	<ul style="list-style-type: none"> • Ultra-compact design • 440 lbs. holding force • Water resistant for indoor and outdoor use

MODELS		List Price
CX-EPD0009	Magnetic Cabinet Lock	\$250.00
BRACKETS		List Price
CX-CL-LZBRK	L&Z Bracket For Use With CX-EPD0009 Magnetic Cabinet Lock	\$57.00
GLASS MOUNT KIT		List Price
CX-CL-GLMNT	Glass Mount Kit For Use With CX-EPD0009 Magnetic Cabinet Lock	\$32.00

Specifications

Power Input:	12 / 24 VDC
Current Draw:	60mA @ 12 VDC 110mA @ 24VDC
Endurance:	250,000 cycles
Static Strength:	440 lbs. (200 kg) Holding Force
Preload:	5 lbs.
Temp. Rating:	-4°F to 140°F (-20°C to 60°C)
Operation Mode:	Fail-Safe
Installation Options:	Front Mount, Side Mount
Dimensions:	
Cabinet Lock:	L Bracket:
2-1/2"H x 27/32"W x 1"D (64mm x 21.5mm x 25mm)	2-1/2"H x 1-3/32"W x 1-1/4"D (64mm x 28mm x 29mm)
Armature Plate:	Z Bracket:
2"H x 11/16"W x 19/32"D (51mm x 18mm x 15.6mm)	2-1/2"H x 1-5/8"W x 3"D (64mm x 41mm x 76mm)
Glass Mount Cover Plate:	Glass Mount Stud Plate:
1"H x 2-1/2"W x 1/16"D (25mm x 64mm x 1mm)	1"H x 2-1/2"W x 5/16"D (25mm x 64mm x 8mm)

CX-ED0010: ELECTROMECHANICAL CABINET LOCK

Camden's CX-ED0010 Electromechanical Cabinet Lock represents an evolution in secure locking systems, designed for a broad range of enclosures that use swinging doors, drawers, and sliding doors. This lock supports both 12V and 24V power supplies and introduces the flexibility of operating in either field selectable fail-safe or fail-secure modes.

The CX-ED0010 accommodates diverse security needs in places such as computer cabinets, lockers, retail display counters, and medical and cannabis dispensaries. Its inclusion of door and lock status sensors further enhances its functionality, providing real-time security status.



Features	
<ul style="list-style-type: none"> • Front mounting for use with office drawers, display cabinets, etc. • Field selectable fail-safe or fail secure operation 	<ul style="list-style-type: none"> • 440 lbs. (200 kg) holding force • Strike plate adjusts to door alignment

MODELS		List Price
CX-ED0010	Electromechanical Cabinet Lock	\$170.00

Specifications

Power Input:	12 / 24 VDC
Current Draw:	280mA @ 12 VDC 140mA @ 24VDC
Endurance:	250,000 cycles
Static Strength:	440 lbs. (200 kg) Holding Force
Temp. Rating:	-4°F to 140°F (-20°C to 60°C)
Operation Mode:	Field Selectable Fail-Safe or Fail Secure
Installation Options:	Front Mount
Door Status Sensor:	200mA @ 30VDC (Max) Form 'C'
Lock Status Sensor:	1A @ 30V DC (Max)
Dimensions:	
	Lock Body:
	3-5/16"H x 1-3/16"W x 1-1/8"D (84mm x 30mm x 28mm)
	Strike Plate:
	2-1/16"H x 15/16"W x 1-1/4"D (52mm x 24mm x 32mm)