LOCKING PRODUCTS

CX-EPD1289L SERIES: 3/4" SURFACE MOUNT FIRE RATED RIM STRIKES WITH PRELOAD

CX-EPD1289L Series 3/4" Grade 1 electric RIM strikes for pullman latches offer the best strike quality, with a preload release function for superior performance under the most demanding conditions. Industry-leading preload strike design registered under U.S. Patent 10,988,959. These award-winning strikes are now also available in a unique all-black finish, including the jaws and latch monitor.

Features

- Up to 15 lbs. of preload pressure
- 3/4" latch projection
- 'Plug-in' latch bolt monitor included
- 'No-cut' surface mount
- Metal mounting jig included
- Tamper resistant stainless steel construction
- Non-handed, with plug-in wiring harness
- Stainless steel cover plate included
- 5 year warranty

MODELS		List Price
CX-EPD1289L	3/4" Surface mount Grade 1 RIM strike with preload, 12/24V, AC/DC, fail safe / fail secure, w/ 'plug-in' latch monitor assembly and metal mounting jig	\$550.00
CX-EPD1289L-BK	All-black finish, surface mount Grade 1 RIM strike with preload, 12/24V, AC/DC, fail safe / fail secure, w/ 'plug-in' latch monitor assembly and metal mounting jig	\$600.00
SPACER PLATE		
CX-EPD1289-SPC	1/8" Spacer plate for CX-EPD1289L surface mount RIM strike	\$20.00
SURFACE MOUNTING BOX List Price		
CX-RIM-SB	Aluminum surface mounted adapter box for mounting Electric RIM Strikes on double doors with RIM Exit Device	\$55.00

Specifications

(UL)

ISTED

UL 1034 UL 294

UL10C/ US CAN4-S104,

LISTED

3hr. Fire rating

Voltage:	12/24V, AC/DC		
Current Draw:	560mA@12VDC 280mA@24VDC		
Strength - Static:	1,500 lbs. Dynamic: 70 Ft- lbs.		
Preload (Fail-Secur	e Only): 15 lbs.		
Endurance:	1,000,000 cycles (Factory Tested) 250,000 cycles (UL verified)		
Mode: Fail-safe / F	ail-secure Duty: Continuous		
Fire Rating: UL10C	/CAN4-S104 3 hrs. (Fail Secure)		
Mechanical Adjustr	nent: Strike Body		
Operation: AC-Buz	z, DC - Silent		
Latch Projection:	3/4"		
Latch Bolt Monitor: SPDT, 100mA @ 24 VDC			
Dimensions (Body)	: 9-3/16"H x 1-7/8"W x 3/4" D (233mm x 48mm x 19.8mm)		