



ELECTRIC STRIKES

LOCKING PRODUCTS

CX-EPD1289L SERIES: 3/4" SURFACE MOUNT FIRE RATED RIM STRIKES WITH PRELOAD

CX-EPD1289L Series 3/4" Grade 1 electric RIM strikes for pullman latches offer the best strike quality, with a preload release function for superior performance under the most demanding conditions. Industry-leading preload strike design registered under U.S. Patent 10,988,959. These award-winning strikes are now also available in a unique all-black finish, including the jaws and latch monitor.



UL10C/
CAN4-S104,
3hr. Fire rating



UL 1034
UL 294



Specifications

Voltage:	12/24V, AC/DC
Current Draw:	560mA @ 12 VDC 280mA @ 24 VDC
Strength - Static:	1,500 lbs. Dynamic: 70 Ft.-lbs.
Preload (Fail-Secure Only):	15 lbs.
Endurance:	1,000,000 cycles (Factory Tested) 250,000 cycles (UL verified)
Mode:	Fail-safe / Fail-secure Duty: Continuous
Fire Rating:	UL 10C/CAN4-S104 3 hrs. (Fail Secure)
Mechanical Adjustment:	Strike Body
Operation:	AC - Buzz, DC - Silent
Latch Projection:	3/4"
Latch Bolt Monitor:	SPDT, 100mA @ 24 VDC
Dimensions:	CX-EPD1289L: 9-3/16"H x 1-15/16"W x 3/4"D (233mm x 49mm x 20mm) CX-RIM-SB: 9-3/16"H x 1-31/32"W x 1-1/4"D (233mm x 50mm x 32mm)

Features	
<ul style="list-style-type: none"> Up to 15 lbs. of preload pressure 3/4" latch projection 'Plug-in' latch bolt monitor included 'No-cut' surface mount Metal mounting jig included 	<ul style="list-style-type: none"> Tamper resistant stainless steel construction Non-handed, with plug-in wiring harness Stainless steel cover plate included 5 year warranty

MODELS		List Price
CX-EPD1289L	3/4" Surface mount Grade 1 RIM strike with preload, 12/24V, AC/DC, fail safe / fail secure, w/ 'plug-in' latch monitor assembly and metal mounting jig	\$675.00
CX-EPD1289L-BK	All-black finish, surface mount Grade 1 RIM strike with preload, 12/24V, AC/DC, fail safe / fail secure, w/ 'plug-in' latch monitor assembly and metal mounting jig	\$725.00
SPACER PLATE		
CX-EPD1289-SPC	1/8" Spacer plate for CX-EPD1289L surface mount RIM strike	\$30.00
FILLER PLATE		
60-35E014	RIM Strike Filler Plate for use with Hager and SDC Exit Devices	\$30.00
SURFACE MOUNTING BOX		
CX-RIM-SB	Aluminum surface mounted adapter box for mounting EPD-1289L (or 1299L) on a double door	\$80.00



CX-EPD1289-SPC



CX-RIM-SB



60-35E014



CX-EPD1299L SERIES: 1/2" SURFACE MOUNT RIM STRIKES WITH PRELOAD

CX-EPD1299L Series 1/2" Grade 1 electric RIM strikes for pullman latches offer the best strike quality, with a preload release function for superior performance under the most demanding conditions. Industry-leading preload strike design registered under U.S. Patent 10,988,959.

Features	
<ul style="list-style-type: none"> • 'Universal' design, UL Security Listed • 1/2" latch projection • 2 Spacer plates included: 1/8" and 1/4" • Stainless steel or all-black finish 	<ul style="list-style-type: none"> • Up to 15 lbs. of preload pressure on strike keepers • Plug-in latch bolt monitor assembly included • 5 year warranty

MODELS		List Price
CX-EPD1299L	1/2" Surface mount Grade 1 RIM, brushed aluminum finish strike with preload, 12/24V, AC/DC, fail safe/fail secure, w/ 'plug-in' latch monitor assembly & metal mounting jig	\$725.00
CX-EPD1299L-BK	1/2" Surface mount Grade 1 RIM strike, all-black finish, w/ preload, 12/24V, AC/DC, fail safe/fail secure, w/ 'plug-in' latch monitor assembly & metal mounting jig	\$760.00
FILLER PLATE		
60-35E014	RIM Strike Filler Plate for use with Hager and SDC Exit Devices	\$30.00
SURFACE MOUNTING BOX		
CX-RIM-SB	Aluminum surface mounted adapter box for mounting EPD-1289L (or 1299L) on a double door	\$80.00



Specifications

Voltage:	12/24V, AC/DC
Current Draw:	560mA @ 12VDC 280mA @ 24VDC
Strength - Static:	1,500 lbs. Dynamic: 70 Ft- lbs.
Preload (Fail-Secure Only):	15 Lbs.
Endurance:	1,000,000 cycles (Factory Tested) 250,000 cycles (UL verified)
Mode:	Fail-safe / Fail-secure Duty: Continuous
Mechanical Adjustment:	Strike Body
Operation:	AC - Buzz, DC - Silent
Latch Projection:	1/2"
Latch Bolt Monitor:	SPDT, 100mA @ 24 VDC
Dimensions:	CX-EPD1299L: 9-3/16"H x 1-15/16"W x 9/16" D (233mm x 49mm x 14mm) CX-RIM-SB: 9-3/16"H x 1-31/32"W x 1-1/4"D (233mm x 50mm x 32mm)



CX-RIM-SB



60-35E014